



AMANI SIGNATURE GLAZE

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION:

A CLEAR, GLAZE COAT. IT IS FORMULATED ON A HIGH-PERFORMANCE ACRYLIC RESIN THAT PROVIDES PROTECTION TO THE PRODUCT IT IS OVERCOATING. IT MAKES THE AMANI PRODUCT BENEATH EASIER TO CLEAN AS IT HAS GOOD RESISTANCE TO DIRT PICK UP DUE TO ITS UNIQUE POLYMERIC STRUCTURE. IT COMES IN AMANI GOLD, AMANI SILVER OR A CLEAR GLAZE.

USE A SKILLED, TRAINED PROFESSIONAL TO APPLY TEXTURED ACRYLIC COATINGS AND GLAZES.

FEATURES & BENEFITS:

- Excellent hardness and mark resistance
- Superior washability and detergent resistance
- Resistance to dirt pickup
- Rapid drying properties
- Being solvent based, provides excellent adhesion and resistant to blanching
- Has excellent abrasion resistance
- Is differentially permeable, having excellent water resistance, yet allowing the coating to "breathe"
- Designed for exterior use as a protective coating over Amani textured coatings.
- Supplied ready to use.

USES:

- **Amani Signature Glaze Coat** is designed as a protective seal over the range of Amani Coatings. It adds a layer of protection and makes the coating easier to clean.

PACKAGING:

5L & 20L Containers

Spread rate: 6 to 8 m² per liter per coat.

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com



AMANI SIGNATURE GLAZE

REFURBISHMENT BUILDING TIPS:

- Prepare the surface by removing all loose and flaking paint, dirt, grease, and grime.
- Make sure plasterwork is sound, dry, and clean.
- Don't skimp on the preparation work, repair cracks, blow holes etc.
- Has the waterproofing been done by a professional?
- Ensure that any scaffolding is positioned at a comfortable distance away from the wall so that the application technique is not compromised. (400-600mm).

NEW BUILD TIPS:

- Prepare the wall to ensure that the surface is clean, dry, and sound.
- Inspect the substrate: The plaster substrate must have a smooth and even finish. This can be achieved with a steel float. The new plaster should be allowed to cure. This may take up to 21 days, depending on weather conditions. Test that it is dry before application. The moisture reader should show a saturation level of less than 12%.

FOR REFURBISHMENT & NEW BUILD:

- Once the chosen Amani Wall Coating has fully cured, at least 24 hours, apply 2 coats of **Amani Signature Glaze** to seal, allow to dry between coats.
- If the building is dusty, clean the walls and allow to dry before applying the glaze.

APPLICATION METHOD:

- Apply 2 coats of **Amani Signature Glaze** to seal.
- Spread rate: 6-8 m²/L/ coat.
- Cross hatch to ensure even coverage.
- Allow to cure between coats.
- Applied by brush or roller.
- The spread rate is a guideline only. The applicator needs to determine the actual spread rate.
- The product is supplied ready for use. DO NOT THIN.
- This product is solvent based. Clean with turpentine.



AMANI SIGNATURE GLAZE

SHELFLIFE AND STORAGE:

- 6 - 8 Months in unopened containers.
- Store in a cool,dry and well ventilated place away from excessive heat or open flame.
- Do not allow to freeze.

CLIMATE CONDITIONS:

- The glaze cannot be exposed to heavy rainfall before it has properly cured (24 hours),
- The coating should never be applied in adverse weather conditions or on wet surfaces.
- In hot temperatures try not to apply in direct sunlight if possible.
- Variations in temperature will affect drying times.

HANDLING AND SAFETY:

This product is based on a proprietary acrylic resin dissolved in a solvent blend which is toxic and flammable. Extreme care must be exercised when using this product. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure the use of aerated ventilation masks. Cured spillages should be gathered up and disposed of in accordance with local authority regulations. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is swallowed.

DISCLAIMER:

All information given here is given in good faith. We reserve the right to make changes to the product in the interests of product development and improving technology

. Any queries please e-mail info@amanicoatings.com

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com
