



AMANI X FORCE PRIMER

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION:

A STRONG, ADHESION PROMOTING PRIMER FOR AMANI TEXTURED ACRYLIC COATINGS

USE A SKILLED, TRAINED PROFESSIONAL TO APPLY TEXTURED ACRYLIC COATINGS

FEATURES & BENEFITS:

- Based on a high-performance acrylic resin and marble dust.
- For interior & exterior use onto suitably prepared substrates
- Superior Alkali Resistance, will not blister
- Controlled water vapor permeability enabling the substrate to “breathe”.
- Deep penetration for excellent adhesion
- Excellent over coating properties
- Eco friendly, water based, LOW VOC LEVEL [30g/L]
- Supplied ready to use

USES:

- **AMANI X FORCE PRIMER** is a strong primer that holds Amani’s heavy plasters on the wall ensuring good adhesion.
- **AMANI X FORCE PRIMER** is designed for interior and exterior use on all suitably prepared substrates. For very dense, porous substrates a different primer may be required. Please discuss with your applicator.
- It is used as a primer coat for Amani Resin Bonded Plasters and Textured Coatings
- **AMANI X FORCE PRIMER** is tinted to match the colour of the topcoat. It is not a direct match so there is no confusion between the primer and finishing coat.

PACKAGING:

8kg, 32kg containers.

Spread rate: 4 m² /Kg

REFURBISHMENT BUILDING TIPS:

- Prepare the surface by removing all loose and flaking paint, dirt, grease, and grime.
- Make sure plasterwork is sound, dry, and clean.
- Don’t skimp on the preparation work, repair cracks, blow holes etc.
- Has the waterproofing been done by a professional?
- Ensure that any scaffolding is positioned at a comfortable distance away from the wall so that the application technique is not compromised. (400-600mm).



AMANI X FORCE PRIMER

NEW BUILD TIPS:

- Prepare the wall to ensure that the surface is clean, dry, and sound.
- Inspect the substrate: The plaster substrate must have a smooth and even finish. This can be achieved with a steel float. The new plaster should be allowed to cure. This may take up to 21 days, depending on weather conditions. Test that it is dry before application. The moisture reader should show a saturation level of less than 12%.

FOR REFURBISHMENT & NEW BUILD:

- Apply 1 even coat of **AMANI X FORCE PRIMER**.
- The applicator needs to assess that the correct primer is being used. Extra preparation may be required once he has reviewed the substrate. **Do not apply on extremely porous substrates.**

APPLICATION METHOD:

- Apply 1 even coat of **AMANI X FORCE PRIMER** and allow to cure.
- Application tools: brush or roller.
- Apply at a spread rate of 4 m² kg.
- Crosshatch to achieve complete obliteration of the substrate
- The spread rate is a guideline only. The applicator needs to determine the actual spread rate.
- The product is supplied ready for use. **DO NOT THIN.**
- Clean with water

SHELFLIFE AND STORAGE:

- 6 - 8 Months in unopened containers.
- Store in a cool dry and well- ventilated place away from excessive heat or open flame.
- Do not allow to freeze.

CLIMATE CONDITIONS:

- The primer cannot be exposed to heavy rainfall before it has properly cured (24 hours),
- The coating should never be applied in adverse weather conditions or on wet surfaces.
- In hot temperatures try not to apply in direct sunlight if possible.
- Variations in temperature will affect drying times.



AMANI X FORCE PRIMER

HANDLING AND SAFETY:

This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to the skin. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages and dispose of in accordance with regulations of the local authorities.

DISCLAIMER:

All information given here is given in good faith. We reserve the right to make changes to the product in the interests of product development and improving technology.

Any queries please e-mail info@amanicoatings.com