



AMANICRETE

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION:

A TINTED, TROWEL APPLIED, TEXTURED PLASTER. AMANICRETE CONTAINS 1.5 MM STONE. THIS ELEGANT FINISH COMES IN A VERTICAL OR RANDOM PATTERN.

USE A SKILLED, TRAINED PROFESSIONAL TO APPLY AMANICRETE

FEATURES & BENEFITS:

- Suitable for interior or exterior use on either new or previously painted walls that have been properly prepared.
- A choice of five colours in the range.
- Eco friendly and water based.
- A hardy, strong, flexible plaster that protects the walls.
- Masks poor quality plasterwork.
- Lasts much longer than paint.
- Supplied ready to use.
- Trowel applied.
- Can be over coated with **Amani Signature Glaze**.

USES:

Designed for interior or exterior use as a protective and decorative coating for a wide variety of new or previously coated surfaces that have been **suitably prepared and primed**.

This includes cement plasters, concrete, fibre cement, ceiling boards, off shutter concrete, highly porous surfaces, gypsum. Special primers might be required for some of these surfaces, discuss with your applicator.

PACKAGING:

8kg, 32kg containers.

Spread rate: 3.0 kg / m²

REFURBISHMENT BUILDING TIPS:

- Prepare the surface by removing all loose and flaking paint, dirt, grease, and grime.
- Make sure plasterwork is sound, dry, and clean.
- Don't skimp on the preparation work, repair cracks, blow holes etc.
- Has the waterproofing been done by a professional?
- Ensure that any scaffolding is positioned at a comfortable distance away from the wall so that the application technique is not compromised. (400-600mm).

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com



AMANICRETE

NEW BUILD TIPS:

- Prepare the wall to ensure that the surface is clean, dry, and sound.
- Inspect the substrate: The plaster substrate must have a smooth and even finish. This can be achieved with a steel float. The new plaster should be allowed to cure. This may take up to 21 days, depending on weather conditions. Test that it is dry before application. The moisture reader should show a saturation level of less than 12%.

FOR REFURBISHMENT & NEW BUILD:

- Apply 1 even coat of **AMANI X FORCE PRIMER**.
- If the surface is very dense or porous apply a good quality trade plaster primer first. In some cases, a universal primer may be required. The applicator needs to assess the primers and preparation required once he has reviewed the substrate.
- Allow to dry and then apply **AMANI X FORCE PRIMER**.
- Apply the **AMANICRETE**.
- The spread rate is 3 kg per square meter. The applicator will need a steel trowel, a plastic trowel, and a dry cloth.
- The spread rate is a guideline only. The applicator needs to determine the actual spread rate.
- The product is supplied ready for use. **DO NOT THIN**.
- Mix gently with a flat paddle before and during application. Do not use a mechanical mixer as this could over develop the colour and/or damage the stone
- Clean with water.

APPLICATION METHOD:

- Apply 1 even coat of **AMANI X FORCE PRIMER** and allow to cure.
- Apply the **AMANICRETE** with a steel trowel and then float with a plastic trowel, use the plastic trowel to make a vertical or random pattern.

SHELF LIFE AND STORAGE:

- 6 - 8 Months in unopened containers.
- Store in a cool dry and well-ventilated place away from excessive heat or open flame.
- Do not allow to freeze.

CLIMATE CONDITIONS:

- Before the coating has cured, 24 hours, the **Amanicrete** cannot be exposed to heavy rainfall.
- The coating should never be applied in adverse weather conditions or on wet surfaces.
- In hot temperatures try not to apply in direct sunlight if possible.
- Variations in temperature will affect drying times.

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com



AMANICRETE

HANDLING AND SAFETY:

This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to the skin. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages and dispose of in accordance with regulations of the local authorities.

DISCLAIMER:

All information given here is given in good faith. We reserve the right to make changes to the product in the interests of product development and improving technology

Any queries please e-mail info@amanicoatings.com

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com
