



AMANISUEDE

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION:

A MODERN DECORATIVE SUEDE-LIKE PLASTER FINISH THAT PROTECTS YOUR WALLS. THE FIBRES FLOW IN DIFFERENT DIRECTIONS BRINGING MOVEMENT TO THE COATING.

USE A SKILLED, TRAINED PROFESSIONAL TO APPLY AMANISUEDE.

FEATURES & BENEFITS:

- Suitable for interior or exterior use on either new or previously painted walls that have been properly prepared.
- Applied to a coating thickness of 1.5mm to 2.0mm throughout.
- If you apply too thinly it won't last as long.
- The thickness can be difficult to gauge, an easy solution is to apply in two thin coats and allow 24 hours drying time between coats.
- Five tinted colours available in the range.
- A hardy, strong, flexible plaster that protects the walls.
- Masks poor quality plasterwork.
- Lasts much longer than paint.
- Supplied ready to use.
- Trowel applied.
- Eco friendly and water based.
- Supplied ready to use.
- Can be over coated with **Amani Signature Glaze**.

USES:

Designed for interior or exterior use as a protective and decorative coating for a wide variety of new or previously coated surfaces that have been **suitably prepared and primed**.

This includes cement plasters, concrete, fibre cement, ceiling boards, off shutter concrete, highly porous surfaces, gypsum. Special primers might be required for some of these surfaces, discuss with your applicator.

It is particularly suitable to accentuate design elements of a structure through imaginative paneling and the creation of contrasting bands.

PACKAGING:

8kg, 32kg containers.

Spread rate: 2.5 to 3.0 kg / m² at a thickness of +/- 1.5

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com



AMANISUEDE

REFURB BUILD TIPS:

- Prepare the surface by removing all loose and flaking paint, dirt, grease, and grime.
- Make sure plasterwork is sound, dry, and clean.
- Don't skimp on the preparation work, repair cracks, blow holes etc.
- Has the waterproofing been done by a professional?
- Ensure that any scaffolding is positioned at a comfortable distance away from the wall so that the application technique is not compromised. (400-600mm).

NEW BUILD TIPS:

- Prepare the wall to ensure that the surface is clean, dry, and sound.
- Inspect the substrate: The plaster substrate must have a smooth and even finish. This can be achieved with a steel float. The new plaster should be allowed to cure. This may take up to 21 days, depending on weather conditions. Test that it is dry before application. The moisture reader should show a saturation level of less than 12%.

FOR REFURBISHMENT & NEW BUILD:

- Apply 1 even coat of **AMANI X FORCE PRIMER** and allow to dry
- If the surface is very dense or porous apply a good quality trade plaster primer first. In some cases, a universal primer may be required. The applicator needs to assess the primers and preparation required once he has reviewed the substrate.
- Apply the **AMANISUEDE**.
- **The spread rate is 2.5 to 3 kg per square meter. The applicator will need a steel trowel, a plastic trowel, and a dry cloth.**
- The spread rate is a guideline only. The applicator needs to determine the actual spread rate.
- The product is supplied ready for use. DO NOT THIN.
- Mix gently with a flat paddle before and during application. Do not use a mechanical mixer as this could over develop the colour and/or damage the stone.
- Clean with water.

APPLICATION METHOD:

- Apply 1 even coat of the **AMANI X FORCE PRIMER** and allow to cure.
- Apply the **AMANISUEDE** with a steel trowel. A 6mm notched trowel is then used to obtain uniform thickness and to remove the excess. The product is then flattened with a steel trowel. Allow the product to flash off, and then pattern with a steel trowel (a busier pattern can be achieved by using a plastic trowel).

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com



AMANISUEDE

APPLICATION METHOD continued:

- Flash off Time: this is the time taken for the product to be touch dry before patterning. This time is critical - if the product is not allowed to flash off, the desired pattern will not be achieved. Flash off time at a thickness of 1.5 to 2.0 mm is about 15-30 minutes and is temperature dependent. A thicker coating will require a longer flash off time.

SHELF LIFE AND STORAGE:

- 6 - 8 Months in unopened containers.
- Store in a cool dry and well- ventilated place away from excessive heat or open flame.
- Do not allow to freeze.

CLIMATE CONDITIONS:

- Before the coating has cured for 24 hours, the **Amanisuede** cannot be exposed to heavy rainfall.
- The coating should never be applied in adverse weather conditions or on wet surfaces.
- In hot temperatures try not to apply in direct sunlight if possible.
- Variations in temperature will affect drying times.

HANDLING AND SAFETY:

This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to the skin. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages and dispose of in accordance with regulations of the local authorities.

DISCLAIMER:

All information given here is given in good faith. We reserve the right to make changes to the product in the interests of product development and improving technology.

Any queries please e-mail info@amanicoatings.com

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com
