



NAIRA

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION:

AMANI's NAIRA IS AN EXCELLENT QUALITY MATT ACRYLIC COATING. A PARTICULAR ADVANTAGE OF NAIRA IS ITS EXCELLENT HIDING PROPERTIES AND THAT IT CAN BE USED TO SELF PRIME.

FEATURES & BENEFITS:

- Excellent obliterating properties
- Easy to clean & user friendly.
- Superior resistance to dirt pickup
- UV and weather resistance
- Non-hazardous
- Non- toxic
- Environmentally friendly

USES:

Designed for interior or exterior use as a protective and decorative coating for a wide variety of new or previously coated surfaces that have been suitably prepared and primed.

This includes cement plasters, concrete, fibre cement, ceiling boards, off shutter concrete, highly porous surfaces, gypsum. Special primers might be required for some of these surfaces. Discuss with your applicator.

PACKAGING:

5 & 20 L containers.

Spread rate: 6-8m²/Lt/coat.

REFURBISHMENT BUILDING TIPS:

- Prepare the surface by removing all loose and flaking paint, dirt, grease, and grime.
- Make sure plasterwork is sound, dry, and clean.
- Don't skimp on the preparation work, repair cracks, blow holes etc.
- Has the waterproofing been done by a professional?
- Ensure that any scaffolding is positioned at a comfortable distance away from the wall so that the application technique is not compromised. (400-600mm).



NAIRA

NEW BUILD TIPS:

- Prepare the wall to ensure that the surface is clean, dry, and sound.
- Inspect the substrate: The plaster substrate must have a smooth and even finish. This can be achieved with a steel float. The new plaster should be allowed to cure. This may take up to 21 days, depending on weather conditions. Test that it is dry before application. The moisture reader should show a saturation level of less than 12%.

FOR REFURBISHMENT & NEW BUILD:

- Apply 1 even coat of **AMANI PLASTER PRIMER** or use one coat of **NAIRA** to self-prime.
- If the surface is very dense or porous a different primer will be required. The applicator needs to assess the primers and preparation required once he has reviewed the substrate.
- The spread rate is 6 to 8 sqm per litre per coat.
- The spread rate is a guideline only. The applicator needs to determine the actual spread rate.
- The product is supplied ready for use. **DO NOT THIN.**
- Clean with water.

APPLICATION METHOD:

- Apply 1 even coat of the appropriate AMANI Plaster Primer or self -prime and allow to cure.
- Apply 2 to 3 coats of AMANI NAIRA in one of 5 standard colours by spray, roller or brush.
- Allow for a drying time, between coats, of 12 to 24 hours.

SHELFLIFE AND STORAGE:

- 6 - 8 Months in unopened containers.
- Store in a cool, dry and well ventilated place away from excessive heat or open flame.
- Do not allow to freeze.

CLIMATE CONDITIONS:

- The paint cannot be exposed to heavy rainfall in the first 24 hours, before the coating has fully cured,
- The coating should never be applied in adverse weather conditions or on wet surfaces.
- In hot temperatures try not to apply in direct sunlight if possible.
- Variations in temperature will affect drying times.



NAIRA

HANDLING AND SAFETY:

This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to the skin. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages and dispose of in accordance with regulations of the local authorities.

DISCLAIMER:

All information given here is given in good faith. We reserve the right to make changes to the product in the interests of product development and improving technology

Any queries please e-mail info@amanicoatings.com