



TOSCA

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION:

AMANI's TOSCA IS AN EXCELLENT QUALITY EXTERIOR ACRYLIC PAINT WITH A LOW SHEEN FINISH. IT IS WASHABLE AND DURABLE.

FEATURES & BENEFITS:

- Superior adhesion to all suitably primed substrates
- Designed for interior or exterior use
- Has excellent impact and abrasion resistance
- Extremely tough and durable
- Easy to clean & user friendly.
- Superior resistance to dirt pickup
- UV and weather resistance
- Non-hazardous
- Non- toxic
- Environmentally friendly

USES:

Designed for interior or exterior use as a protective and decorative coating for a wide variety of new or previously coated surfaces that have been suitably prepared and primed.

This includes cement plasters, concrete, fiber cement, ceiling boards, off shutter concrete, highly porous surfaces, gypsum. Special primers might be required for some of these surfaces. Discuss with your applicator.

PACKAGING:

5 & 20 L containers.

Spread rate: 7-9 m²/Lt/coat.

REFURB BUILD TIPS:

- Prepare the surface by removing all loose and flaking paint, dirt, grease, and grime.
- Make sure plasterwork is sound, dry, and clean.
- Don't skimp on the preparation work, repair cracks, blow holes etc.
- Has the waterproofing been done by a professional?
- Ensure that any scaffolding is positioned at a comfortable distance away from the wall so that the application is not compromised. (400-600mm).

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com



TOSCA

NEW BUILD TIPS:

- The plaster substrate must conform to a smooth and even finish. This can be achieved with a fine wood float or a steel float.
- Adequate time should be allowed for plaster to cure (*confirm a moisture reading of <12 % : this may take up to 21 days, depending on weather conditions*).
- Prepare the substrate appropriately to ensure that the surface is clean, dry, sound, and free of defects.
- Ensure that the scaffold is positioned at a comfortable distance away from the surface so that application technique is not compromised (400-600mm).
- Check spread rates & tools beforehand.
- The product is supplied ready for use. **DO NOT THIN.**
- Clean with water.

APPLICATION METHOD:

- Apply 1 even coat of the appropriate **AMANI ACRYLIC PLASTER PRIMER** and allow to cure for 24 hours.
- Apply 2 to 3 coats of **AMANI TOSCA** in a choice of 5 standard colours. Apply by spray, roller, or brush. Allow for drying time between coats.

SHELF LIFE AND STORAGE:

- 6 - 8 Months in unopened containers.
- Store in a cool dry and well-ventilated place away from excessive heat or open flame.
- Do not allow to freeze.

HANDLING AND SAFETY:

This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to the skin. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages and dispose of in accordance with regulations of the local authorities.

DISCLAIMER:

All information given here is given in good faith. We reserve the right to make changes to the product. In the interests of product development and improving technology.

Any queries please e-mail info@amanicoatings.com

Phone
+27 21 797 4250

Amani Coatings (Pty) Ltd
Reg. No. Rep. South Africa
1998/020176/07

info@amanicoatings.com
www.amanicoatings.com
